



**INTREPID** LOADER

# SAVE TIME & MONEY AND GO ARTICULATING

The Intrepid miniloader as offered by Miniloaders.com is manufactured by the Belgian manufacturer Knikmops, who have manufactured compact wheel-loaders for the western European market since 1997. Most of their machines go to paving companies where they see long service

lives under hard working conditions. Intrepid loaders are ideally suited for companies in the green and hardscaping industry. We have experience in equipping and configuring these machines for tree care, landscape and other jobsites.



801 East Second Street  
Hereford, 79045 TX, USA

Phone: 806 – 283 – 0620  
Email: [info@miniloaders.com](mailto:info@miniloaders.com)

**MINILO**  **ADERS**.com



# INTREPID MINI LOADERS

Mini-skidsteer type hitch,  
high-quality Belgian manufacturing

- Highly versatile and maneuverable
- High-quality components
- Comfortable handling
- Cost-efficient



## INTREPID KM85

ENGINE	23HP Kubota (3 cyl. D902 diesel)
SERVICE WEIGHT	1970 lbs.
LIFTING CAPACITY	1540 lbs.
LIFT CAP. 20" FRONT OF WHEELS	1000 lbs
DRIVING SPEED	0-8 mp/h
LIFTING HEIGHT (HINGE POINT)	74.6 in. / 6.2 ft.
LENGTH WITHOUT ATTACHMENT	98.4 in. / 8.2 ft.
WIDTH	40 in. (standard tires)
AUX. HYDRAULICS	7.4 GPM / 2600 PSI
DRIVE	Hydrostatic 4WD with automotive control through 4 wheel motors. Drive direction through joystick button. RPM regulated with foot pedal.



## INTREPID KM100 TELE

ENGINE	25HP Kubota (3 cyl. D1105 diesel)
SERVICE WEIGHT	3050 lbs.
LIFTING CAPACITY	1760 lbs.
LIFT CAP. 20" FRONT OF WHEELS	990 lbs
DRIVING SPEED	0-11 mp/h
LIFTING HEIGHT (HINGE POINT)	116.7 in. / 9.7 ft.
LENGTH WITHOUT ATTACHMENT	110.6 in. / 9.2 ft.
WIDTH	49.5 in. (dual wheel option available)
AUX. HYDRAULICS	7.4 GPM / 2600 PSI
DRIVE	Hydrostatic 4WD with automotive control through 4 wheel motors. Drive direction through joystick button. RPM regulated with foot pedal or lever.



## INTREPID KM130 TELE

ENGINE	25HP Kubota (4 cyl. v1505 diesel)
SERVICE WEIGHT	3980 lbs.
LIFTING CAPACITY	2425 lbs.
LIFT CAP. 20" FRONT OF WHEELS	1850 lbs
DRIVING SPEED	0-12.5 mp/h
LIFTING HEIGHT (HINGE POINT)	126 in. / 10.5 ft.
LENGTH WITHOUT ATTACHMENT	120.4 in. / 10 ft.
WIDTH	52 in. (dual wheel option available)
AUX. HYDRAULICS	9.8 GPM / 2600 PSI
DRIVE	Hydrostatic 4WD with automotive control through 4 wheel motors. Drive direction through joystick button. RPM regulated with foot pedal or lever.

VISIT **MINILOADERS**.com

Phone: 806 – 283 0620 | Email: [info@miniloaders.com](mailto:info@miniloaders.com)