



INTREPID LOADER

SAVE TIME & MONEY AND GO ARTICULATING

The Intrepid miniloader as offered by Miniloaders.com is manufactured by the Belgian manufacturer Knikmops, who have manufactured compact wheel-loaders for the western European market since 1997. Most of their machines go to paving companies where they see long service

lives under hard working conditions. Intrepid loaders are ideally suited for companies in the green and hardscaping industry. We have experience in equipping and configuring these machines for tree care, landscape and other jobsites.



Cincinnati, OH Phone: 513-237-1732 Email: info@miniloaders.com

MINILO  **ADERS**.com

INTREPID MINI LOADERS



MINILOADERS.COM



Mini-skidsteer type hitch,
high-quality Belgian
manufacturing

- > Highly versatile
and maneuverable
- > High-quality
components
- > Comfortable handling
- > Cost-efficient

INTREPID KM85

ENGINE	23HP Kubota (3 cyl. D902 diesel)
SERVICE WEIGHT	1970 lbs.
LIFTING CAPACITY	1540 lbs.
LIFT CAP. 20" FRONT OF WHEELS	1000 lbs
DRIVING SPEED	0-8 mp/h
LIFTING HEIGHT (HINGE POINT)	74.6 in. / 6.2 ft.
LENGTH WITHOUT ATTACHMENT	98.4 in. / 8.2 ft.
WIDTH	40 in. (standard tires)
AUX. HYDRAULICS	7.4 GPM / 2600 PSI
DRIVE	Hydrostatic 4WD with 4 wheel motors.

INTREPID KM100 TELE

ENGINE	25HP Kubota (3 cyl. D1105 diesel)
SERVICE WEIGHT	3050 lbs.
LIFTING CAPACITY	1760 lbs.
LIFT CAP. 20" FRONT OF WHEELS	990 lbs
DRIVING SPEED	0-11 mp/h
LIFTING HEIGHT (HINGE POINT)	116.7 in. / 9.7 ft.
LENGTH WITHOUT ATTACHMENT	110.6 in. / 9.2 ft.
WIDTH	49.5 in. (dual wheel option available)
AUX. HYDRAULICS	7.4 GPM / 2600 PSI
DRIVE	Hydrostatic 4WD with 4 wheel motors.



INTREPID KM130 TELE

ENGINE	25HP Kubota (4 cyl. V1505 diesel)
SERVICE WEIGHT	3980 lbs.
LIFTING CAPACITY	2425 lbs.
LIFT CAP. 20" FRONT OF WHEELS	1850 lbs
DRIVING SPEED	0-12.5 mp/h
LIFTING HEIGHT (HINGE POINT)	126 in. / 10.5 ft.
LENGTH WITHOUT ATTACHMENT	120.4 in. / 10 ft.
WIDTH	52 in. (dual wheel option available)
AUX. HYDRAULICS	9.8 GPM / 2600 PSI
DRIVE	Hydrostatic 4WD with 4 wheel motors.



INTREPID KM180 TELE

ENGINE	43HP Yanmar (3 cyl. 3TNV86CT)
SERVICE WEIGHT	5000 lbs.
LIFTING CAPACITY	2866 lbs.
LIFT CAP. 20" FRONT OF WHEELS	2535 lbs
DRIVING SPEED	0-12.5 mp/h
LIFTING HEIGHT (HINGE POINT)	130 in. / 10.8 ft.
LENGTH WITHOUT ATTACHMENT	127.5 in. / 10.6 ft.
WIDTH	56 in.
AUX. HYDRAULICS	13.2 GPM / 2600 PSI
DRIVE	Hydrostatic 4WD with 4 wheel motors.



INTREPID KM250 TELE

ENGINE	48HP Yanmar (4 cyl. 4TNV88C)
SERVICE WEIGHT	6000 lbs.
LIFTING CAPACITY	5280 lbs.
LIFT CAP. 20" FRONT OF WHEELS	3600 lbs
DRIVING SPEED	0-12.5 mp/h
LIFTING HEIGHT (HINGE POINT)	140 in. / 11.6 ft.
LENGTH WITHOUT ATTACHMENT	135.4 in. / 11.3 ft.
WIDTH	65 in. (dual wheel option available)
AUX. HYDRAULICS	16.5 GPM / 2600 PSI
DRIVE	Hydrostatic 4WD with 4 wheel motors.